


Datasheet

DC connector

BC03H,female,terminals crimping, non rewirable.housing color,black



Art.No.	BC03H-F-C24
Order unit	PCS

Approvals



Technical data

General

Rated current	30A (TUV) , 35A (CSA)
Rated voltage	1100V DC (TUV, CSA)
Contact resistance	$\leq 0.5m\Omega$
Insulation resistance	$\geq 400M\Omega$
Rated impulse withstand voltage	6600V
Over-voltage category	III
Pollution degree	2
Waterproof Rating	IP67 (mated)
Flammability Rating	UL94-V0
IEC protection class	II
Rated temperature	-40°C~+85°C
Maximum operating temperature	115°C

Connection Data

Number of contacts	01 Pin
Applicable wire gauge	2.5/4.0/6.0mm ² or 14/12AWG
Outer cable diameter	5~6.8mm

Model

Connector Gender	Female
Backshell Assembly Style	Straight crimp

Material

Housing material	PC (Polycarbonate)
Contact Material	Red Copper(punching) / CuZn alloy(cutting)
Contact Surface	Tin-plated
Sealing gasket	Silicon

Standards

EN 62852: 2014	IEC - Safety requirements and tests
UL6703	USA and Canada - Safety requirements and tests
RoHS compliant	Yes

Dimensions

Length	59.2mm
Width	19.0mm
Height	19.0mm
Weight	9.53g

REV. 05
2023.12.19

Wuxi Betteri Electronic Technology CO.,LTD. | Wuxi Optoelectronic Materials
Science&Technology Pack 5-1,#11,Jinshan Rd.Branch#4,Wuxi,China | Tel : 0086-0510-88771606
Fax : 0086-0510-88770676 | Zip code : 214037 | Website <http://www.betteri.cn>

Your better choice